


## DIN STANDARD CONNECTIONS


### M21512

METRIC O-RING FEMALE 24° CONE LIGHT DUTY - DIN 20066 / ISO 12151-2 (THRUST-WIRE NUT)  
 HEMBRA METRICA CON O-RING ASIEN TO A 24° SERIE LIGERA DIN 20066 / ISO 12151-2 (TUERCA CON SEGURO)  
 DKOL - DIN 20066 / ISO 12151-2 (GESTIFTETE MUTTER)  
 FEMMINA METRICA CONO 24° O-RING SERIE LEGGERA DIN 20066 / ISO 12151-2 (DADO SPINATO)



### M21513

METRIC O-RING FEMALE 24° CONE LIGHT DUTY - DIN 20066 / ISO 12151-2 (SLIP-ON NUT)  
 HEMBRA METRICA CON O-RING ASIEN TO A 24° SERIE LIGERA DIN 20066 / ISO 12151-2 (TUERCA LIBRE)  
 DKOL - DIN 20066 / ISO 12151-2 (HINTERLEGTE MUTTER)  
 FEMMINA METRICA CONO 24° O-RING SERIE LEGGERA DIN 20066 / ISO 12151-2 (DADO PASSANTE)



PART. REF.	HOSE BORE		THREAD	PIPE	DIMENSIONS mm					
	DN	inch			T	mm	B	A	C	H <sub>2</sub>
M21513-03-12	5	3/16"	- 03	M 12x1,5	6	3,0	21,9	1,7		14
M21513-03-14	5	3/16"	- 03	M 14x1,5	8	4,5	24,5	1,7		17
M21512-04-12	6	1/4"	- 04	M 12x1,5	6	3,0	21,1	2,2		17
M21513-04-14	6	1/4"	- 04	M 14x1,5	8	4,0	22,1	1,7		17
M21513-04-16	6	1/4"	- 04	M 16x1,5	10	6,0	22,6	2,1		19
M21513-04-18	6	1/4"	- 04	M 18x1,5	12	7,0	21,9	2,3		22
M21512-05-14	8	5/16"	- 05	M 14x1,5	8	4,0	20,0	1,7		17
M21513-05-16	8	5/16"	- 05	M 16x1,5	10	6,0	22,6	2,1		19
M21513-05-18	8	5/16"	- 05	M 18x1,5	12	7,0	21,9	2,3		22
M21512-06-16	10	3/8"	- 06	M 16x1,5	10	6,0	23,1	3,0		19
M21513-06-18	10	3/8"	- 06	M 18x1,5	12	7,0	22,4	2,3		22
M21513-06-22	10	3/8"	- 06	M 22x1,5	15	9,3	25,0	2,3		27
M21512-08-18	12	1/2"	- 08	M 18x1,5	12	7,0	29,0	2,9		22
M21513-08-22	12	1/2"	- 08	M 22x1,5	15	9,3	25,4	2,3		27
M21513-08-26	12	1/2"	- 08	M 26x1,5	18	12,5	26,1	2,5		32
M21512-10-18	16	5/8"	- 10	M 18x1,5	12	7,0	29,0	2,9		22
M21512-10-22	16	5/8"	- 10	M 22x1,5	15	9,5	26,5	2,4		27
M21513-10-26	16	5/8"	- 10	M 26x1,5	18	12,5	26,0	2,5		32
M21513-10-30	16	5/8"	- 10	M 30x2	22	15,0	34,0	3,6		36
M21513-10-36	16	5/8"	- 10	M 36x2	28	20,0	30,5	3,8		41
M21512-12-26	19	3/4"	- 12	M 26x1,5	18	12,5	31,1	3,6		32
M21513-12-30	19	3/4"	- 12	M 30x2	22	15,0	28,2	3,6		36
M21513-12-36	19	3/4"	- 12	M 36x2	28	20,0	28,3	3,8		41
M21512-16-30	25	1"	- 16	M 30x2	22	15,0	34,0	3,6		36
M21513-16-36	25	1"	- 16	M 36x2	28	19,8	29,4	3,8		41
M21513-16-45	25	1"	- 16	M 45x2	35	26,0	39,0	5,1		50
M21512-20-36	31	1,1/4"	- 20	M 36x2	28	19,8	35,5	5,0		41
M21513-20-45	31	1,1/4"	- 20	M 45x2	35	26,0	32,9	5,1		50
M21513-20-52	31	1,1/4"	- 20	M 52x2	42	32,0	32,5	5,1		60
M21512-24-45	38	1,1/2"	- 24	M 45x2	35	26,0	42,5	5,8		50
M21513-24-52	38	1,1/2"	- 24	M 52x2	42	32,0	32,8	5,1		60