


## DIN STANDARD CONNECTIONS


### M21612

METRIC O-RING FEMALE 24° CONE HEAVY DUTY  
 DIN 20066 / ISO 12151-2 (THRUST-WIRE NUT)  
 HEMBRA METRICA CON O-RING ASIETO A 24° SERIE PESADA  
 DIN 20066 / ISO 12151-2 (TUERCA CON SEGURO)  
 DKOS - DIN 20066 / ISO 12151-2 (GESTIFTETE MUTTER)  
 FEMMINA METRICA CONO 24° O-RING SERIE PESANTE  
 DIN 20066 / ISO 12151-2 (DADO SPINATO)



### M21613

METRIC O-RING FEMALE 24° CONE HEAVY DUTY - DIN 20066 / ISO 12151-2 (SLIP-ON NUT)  
 HEMBRA METRICA CON O-RING ASIETO A 24° SERIE PESADA  
 DIN 20066 / ISO 12151-2 (TUERCA LIBRE)  
 DKOS - DIN 20066 / ISO 12151-2 (HINTERLEGTE MUTTER)  
 FEMMINA METRICA CONO 24° O-RING SERIE PESANTE  
 DIN 20066 / ISO 12151-2 (DADO PASSANTE)



PART. REF.	HOSE BORE	THREAD	PIPE	DIMENSIONS mm						
------------	-----------	--------	------	---------------	--	--	--	--	--	--

	DN	inch	Size	T	mm	B	A	C			H <sub>2</sub>
M21613-03-14	5	3/16"	- 03	M 14x1,5	6	2,5	25,5	3,5			17
M21613-03-16	5	3/16"	- 03	M 16x1,5	8	3,2	21,9	3,4			19
M21613-04-14	6	1/4"	- 04	M 14x1,5	6	3,0	23,5	3,5			17
M21613-04-16	6	1/4"	- 04	M 16x1,5	8	4,0	22,2	3,4			19
M21613-04-18	6	1/4"	- 04	M 18x1,5	10	4,0	28,0	3,0			22
M21613-04-20	6	1/4"	04	M 20x1,5	12	7,0	25,7	2,5			24
M21613-05-18	8	5/16"	- 05	M 18x1,5	10	5,5	28,0	3,0			22
M21613-05-20	8	5/16"	- 05	M 20x1,5	12	5,5	24,8	2,5			24
M21613-06-18	10	3/8"	- 06	M 18x1,5	10	7,0	28,5	3,0			22
M21613-06-20	10	3/8"	- 06	M 20x1,5	12	7,0	25,3	2,5			24
M21613-06-22	10	3/8"	- 06	M 22x1,5	14	7,0	32,6	3,0			27
M21613-06-24	10	3/8"	- 06	M 24x1,5	16	7,0	32,0	3,0			30
M21612-08-20	12	1/2"	- 08	M 20x1,5	12	7,0	29,0	2,5			24
M21612-08-22	12	1/2"	- 08	M 22x1,5	14	7,0	27,5	2,5			27
M21613-08-24	12	1/2"	- 08	M 24x1,5	16	9,3	26,7	3,0			30
M21613-08-30	12	1/2"	- 08	M 30x2	20	12,5	37,0	3,5			36
M21612-10-24	16	5/8"	- 10	M 24x1,5	16	9,3	29,5	4,0			30
M21613-10-30	16	5/8"	- 10	M 30x2	20	12,5	30,6	3,5			36
M21613-10-36	16	5/8"	- 10	M 36x2	25	15,0	40,0	4,5			41
M21612-12-24	19	3/4"	- 12	M 24x1,5	16	9,3	30,5	4,0			30
M21612-12-30	19	3/4"	- 12	M 30x2	20	12,5	33,5	2,2			36
M21613-12-36	19	3/4"	- 12	M 36x2	25	15,0	34,1	4,5			41
M21612-16-30	25	1"	- 16	M 30x2	20	12,5	34,5	2,2			36
M21612-16-36	25	1"	- 16	M 36x2	25	15,0	35,3	1,7			41
M21613-16-42	25	1"	- 16	M 42x2	30	19,8	35,4	6,3			50
M21613-20-52	31	1,1/4"	- 20	M 52x2	38	26,0	37,5	8,0			60
M21613-24-52	38	1,1/2"	- 24	M 52x2	38	26,0	49,6	8,0			60